



## กล้อง IP รุ่น JET-007 IR Pan and Tilt (CF Card Support)



Front Camera



Back Camera

### Features:

- LCD display the IP address
- Moving set: move 120 degrees up and down, 180 degrees left to right
- Supports three kinds of network connection methods; fixed IP, DHCP, and PPPoE
- Six infrared LED, automatic operate in dark environment
- FTP server storage
- Storage pictures and video at the visit position PC
- Image sensor: CMOS, VGA, 1/4 inches
- Lens: high and clear degree CCD lens
- Infrared LED: supports 6 infrared LED, automatic operate in dark environment
- Resolution: VGA (640 x 480)/CIF (320 x 240)/the QCIF (160 x 120)
- Compress format: M-JPEG
- Frame rate: 30fps under the better bandwidth condition
- Moving set: control moving set in the distance, move 120 degrees up and down, 180 degrees left to right
- Display: LCD display the IP address /Network mask/gateway IP
- Storage mode: storage picture use CF card socket, supports maximum 2GB CF card
- Input/output port: connect 2 switches sensor outside and 1 relay output to alarms
- Moving detection: moving detection and alarms features
- Video transmission: support 10 customers to visit at the same time
- Visit: built-in web server, visit the IP camera directly through the web browser
- Certification/encryption: visit the IP camera use password 3 classes visit authority setting
- Network protocol: CP/ IP, UDP, IMCP, SMTP, HTTP, FTP, DNS, the DDNS DHCP, Pope
- Network connections: Ethernet 10/100Base-T, RJ-45 connector
- Software: 16 picture tracking

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ  
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434  
Email: [kitti@sone.co.th](mailto:kitti@sone.co.th)  
[www.sone.co.th](http://www.sone.co.th)



Specification:

Web Transmission	MJPEG
Image Sensor	1/4"CMOS
Lens	3.6 mm@F2.0
Max. Video Resolution(Pixels)	640x480, 320x240, 160x120
Video Adjust	Brightness, Contrast
Image Quality	Low, Normal, High
Rotation	Rotate, Mirror, Normal, Flip
Surveillance Viewing	Internet Explorer Browser, Mozilla Firefox
Client Recording Software	Vilar Multi-view (Max 16 Cam recording)
Pan Control	180° Manual, Auto
Tilt	120° Manual, Auto
IR Led	6 Infrared LEDs
Quick Snap Shot	Yes (JPEG File)
Interface	RJ-45
Networking Protocol	Protocols TCP/IP, HTTP, SMTP, FTP, PPPoE, DHCP, NTP, DNS, DDNS
CF Card Support	Yes (2GM Max.)
Digital Input/Output	Yes (2/1)
Triggered Action	Mail, FTP, CF Card Save
Light Frequency/Exposure	50-60 Hz
Security	3 Level Admin User Guest
Power Supply	DC 5V 2A 5W
System Firmware Update	HTTP mode, can be updated remotely

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ  
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434  
Email: [kitti@sone.co.th](mailto:kitti@sone.co.th)  
[www.sone.co.th](http://www.sone.co.th)