



## **กล้อง IP Camera รุ่น PP-101W Plug and Play Fix CMOS**



### **Features:**

- Plug & Play
- No More DDNS Setting or IP Mapping
- Easy Access to the Camera via the Internet
- Software to Manage 16 IP Cameras
- Built-in Web Server
- Support Enhanced MPEG-4 Compression
- High Resolution Up to 640x480 pixels
- Email Notification for Motion Detection
- Upload Image to FTP
- 3G Cellphone Viewing
- Synchronized Audio Monitoring
- Unicast to 4 Users Simultaneously
- Multicast Up to Unlimited Users Simultaneously
- Online Firmware Upgrade
- Watchdog Function

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ  
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434  
Email: [kitti@sone.co.th](mailto:kitti@sone.co.th)  
[www.sone.co.th](http://www.sone.co.th)

**Specification:**

<b>Item No.</b>	PP-101W	
<b>Network Interface</b>	Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45	
<b>Wireless Interface (Wireless Model)</b>	IEEE 802.11g 6 - 54 Mbps IEEE 802.11b 1 - 11 Mbps	
	<b>Transmission Power</b>	14.5dBm typically @ 802.11g 17.5dBm typically @ 802.11b
	<b>Receiver Sensitivity</b>	54Mbps: Typical -73dBm @ 10% PER
		11Mbps: Typical -86dBm @ 10% PER
	Modes: Infrastructure and ad-hoc	
	Antenna gain: 1.8 dBi	
<b>Image Sensor</b>	RGB VGA 1/5 inch CMOS Automatic Exposure Control, Automatic White Balance, Automatic Gain Control, Automatic Brightness Control	
<b>Light Sensitivity</b>	1.0 V/Lux-sec	
<b>Lens</b>	3.2 mm, F2.4, Viewing Angle: 63° Fixed Iris, Focus Range:0.5 m to infinity	
<b>Video Compression</b>	MPEG-4 Part 2 (ISO/IEC 14496-2) with Motion Detection,	
<b>Video Streaming</b>	MPEG-4 (Controllable Frame Rate and Bandwidth)	
<b>Resolutions</b>	160x120, 320x240, 640x480	
<b>Frame Rate</b>	Up to 30 fps in All Resolutions	
<b>Audio</b>	Built-in Microphone for Audio Monitoring	
	Audio Compression: MP2, G.726 ADPCM 32 kbit/s	
<b>Security</b>	Web Management Username/Password Protection	
	Video Display ID/Password Protection	
	WiFi WEP and WPA Security Mode (Wireless Model)	
<b>Supported Protocols</b>	IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, IGMP, RTCP,SMTP, FTP, DHCP, UPnP, ARP, DNS, and PPPoE	
<b>Management</b>	Web-based Configuration	
<b>Video Management Software</b>	Surveillance Application for Viewing and Archiving Up to 16 IP Cameras	
<b>Hardware Requirements</b>	Pentium 4 CPU 1.0 GHz or higher, or equivalent AMD 256 MB RAM	
<b>Supported Operating System</b>	Microsoft Windows XP SP2 or above, Framework 2.0	
<b>Users</b>	Up to 4 Simultaneous Users (Unicast)	
	Unlimited Users in Multicast	
<b>Alarm and Event Management</b>	Events Triggered by Video Motion Detection Notification by Email / Upload JPEG Images to FTP	
<b>Power Source</b>	DC 5V, 1A	
<b>Dimensions</b>	125 mm x 75 mm x 35 mm,	
<b>Weight</b>	260 g (including camera bracket, excluding power adaptor)	
<b>Operating Conditions</b>	Temperature 0-50 °C	
	Humidity 20 - 80% RH (non-condensing)	

**สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ**  
**บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434**  
**Email: [kitti@sone.co.th](mailto:kitti@sone.co.th)**  
[www.sone.co.th](http://www.sone.co.th)