

# 2 MEGA FULL HD IP BOX CAMERA


## YUC-H626

### Feature

- Full HD 1080P 30 FPS Real Time
- H.264/MPEG-4/M-JPEG triple streams
- Up to 32G SD card recording for alarm trigger & network outage
- ICR built in / Day&Night Switch time control manual
- 2-way audio
- Mobile view support
- Digital Wide Dynamic Range / Shutter Speed adjustment
- WiFi / PoE Support



Server	Compression	Triple streams : H.264/MPEG-4/JPEG
	Pixel (H x V)	1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144
	Traffic Control	32/48/64/96/128/192/256/320/384/448/512/576/640/704/768Kbps
	Max. Frame Rate	(30fps) 1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144
	Safety	User-ID and password
	Protocols	Ipv4/v6 / HTTP / HTTPS / QoS Layer 3 level / FTP / SMTP / Bonjour / UPnP / SNMPv1/v2c/v3 / DNS/DDNS / NTP / RTSP / RTP / UDP / IEEE 802.1x / DHCP / Access list filtering
	Number of User	Max. 10 connections for singal video
	Storage Capacity	SD card / FTP / NAS (Samba)
	Alerting	SMTP / FTP / HTTP / SD Card
	Pre / Post Alarm	Pre (0,1,2,3,4,5) / Post (0,1,2,3,4,5,10) seconds
Network Camera	Release for alarm	Motion detection/ I/O / schedule
	Image Pick-up Device	1/2.7" Progressive scan CMOS sensor 2 Mega pixel
	D-WDR	Off & 1~8 level
	Shutter Time	outdoor / indoor / 1/30, 1/50, 1/60, 1/100, 1/125, 1/250, 1/500, 1/1000
	Video Output	BNC (1Vp-p, 75 Ohms)
	Min Illum	0.1 Lux (color) / 0.05 Lux (B/W)
	Optical Lens	CS mount (DC driver)
Audio	Day / Night	Light Sensor Mode / Color Mode(Day) / B/W Mode(Night) / Times Mode / Synchronize with DI input
	Audio	2-way-halfduplex
	Audio Compression	G.711(64Kbps) / G.726(24Kbps) / G.726(32Kbps)
	Adjust Volume	Mic-in / Line-out web adjustable
	Audio In	Mic built-in
Terminal	Audio Out	3.5mm phone jack (Support 2way)
	Network Interface	Ethernet (10Base-T/100Base-Tx) / PoE / WiFi (802.11/b/g/n)
	Video Interface	BNC, Video composit (NTSC/PAL)
	External Port	Alarm in / Relay out
General	SD Card	SD card (up tp 32GB)
	Operation Voltage	12V DC : max. 3.8W / 24V AC : max. 4.3W PoE(802.3af above) : max. 4.8W
	Dimen./Weight	65mm (W) x 58mm (H) x 132mm (L) / @ 500g / 12pcs per carton
	Operation Temp.	-10°C ~ +45°C



Certificate : CE , FCC , RoHS

\*No SD card slot & local storage function for Argentina