

2MP IP CUBE CAMERA

YUC-HC26A

Feature

- Anti-fog / Corridor mode / Distortion correction
- Tampering detection
- Passive infrared sensor(PIR)
- WPS support
- Mobile view support(Push video)
- PoE support / WiFi(Optional)
- Onvif compliant
- SD card support continuous recording up to 64G



| | | |
|-------------------|--|--|
| Server | Compression | H.264 / MJPEG |
| | Resolution | 1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144 |
| | Traffic Control | 32K ~ 8Mbps |
| | Max. Frame Rate | (30fps)1920x1080 |
| | Safety | User-ID and password |
| | Protocols | Ipv4/v6 / HTTP / HTTPS / QoS Layer 3 level / FTP / SMTP / Bonjour / UPnP / SNMPv1/v2c/v3 DNS/DDNS / NTP / RTSP / RTP / UDP / IEEE 802.1x / DHCP / Access list filtering |
| | Number of User | Max. 10 connections |
| | Storage Capacity | Micro SD / FTP / NAS(Samba) |
| | Alerting | SMTP / FTP / HTTP / Micro SD |
| | Pre / Post Alarm | Pre(0,1,2,3,4,5) / Post(0,1,2,3,4,5,10)seconds |
| Release for alarm | Motion detection/ I/O / Schedule / Tampering detection | |
| Network Camera | Sensor | 1/2.7" Megapixel CMOS sensor |
| | Optical Lens | 2.8mm / F2.0 |
| | View Angle | 111.10°(H) , 65.10°(V) |
| | D-WDR | Off & 1~8 level |
| | AGC | 8X ~ 64X |
| | Shutter Time | Outdoor / Indoor / 1/30 , 1/50 , 1/60 , 1/100 , 1/125 , 1/250 , 1/500 , 1/1000 |
| | Min Illum | 0.1 Lux(Color) / 0.05 Lux(B/W) |
| | IR LED / Range | 6pcs / 5M |
| | Day / Night | Light sensor mode / Color mode(Day) / B/W mode(Night) / Times mode / Synchronize with DI Input |
| Audio | Audio | 2-way half duplex |
| | Audio Compression | G.711(64Kbps) / G.726(24Kbps) / G.726(32Kbps) |
| | Adjust Volume | Mic-in / Line-out web adjustable |
| | Audio In | Mic built-in(Support 2-way) |
| | Audio Out | 3.5mm phone jack, or Speaker(Support 2-way) |
| Terminal | Network Interface | Ethernet(10Base-T/100Base-Tx) / PoE / WiFi-802.11(b/g/n) |
| | External Port | DI / DO |
| | SD Card | Micro SD(Up to 64GB) |
| General | Operation Voltage | DC 12V Max: 3W(IR on) / 2.52W(IR off) PoE Max: 3.84W(IR on) / 3.36W(IR off) |
| | Dimen./Weight | 67(W) x 112(L) x 36.4(H) mm / 310g |
| | Operation Temp. | -10°C ~ +45°C |



Lens Distortion Correction

Certificate : CE , FCC , RoHS

*No SD card slot & local storage function for Argentina