



Plug and Play MPEG4 Video Server



Alternate Views



Features:

- Convert analog CCTV camera into network camera.
- Support NTSC and PAL video input format
- Built-in micro-SD card interface for video storage on SD card.
- DI/DO for alarm detection/triggering.
- Free 36 channel management software(VMS) bundled.
- Software for 3G phone monitoring.
- NAS storage support, "NAS scan" function for easy configuration.
- RS485 interface for pan/tilt control (Pelco-P/Pelco-D).

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434
Email: kitti@sone.co.th
www.sone.co.th



Specification:

Power	Input DC 12V, 300 mA.
Network interface	Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45
Video interface	1 analog video input and 1 analog video output CVBS composite BNC connector, 1.0Vp-p with 75 ohm loading
Serial interface	1 RS-485 interface for pan/tilt control, support Pelco-P, Pelco-D protocol. (will be available after firmware v020203)
D/I D/O interface	1 D/I for alarm detection 1 D/O for alarm triggering
Micro-SD card interface	Micro-SD card interface for local video storage The supported Micro SD-Card capacity is up to 16G bytes.
Rest button interface	One reset button interface, to factory default settings
Led Indicator	1 LED for internet connection status indication 1 LED for Ethernet connection indication Enable/disable - web configurable
Processors	RISC CPU, hardware video processing and compression.
Video compression	MPEG-4 Part 2 (ISO/IEC 14496-2) with motion detection. Profiles: Simple Profile, level 0-3
Frame rate	Up to 30 fps in all resolutions
Video streaming	MPEG-4 Separate frame rate/resolution/bandwidth settings for PC and mobile.
Video settings	Resolution: D1(720x480 for NTSC, 720x576 for PAL), CIF(352x240 for NTSC, 352x288 for PAL), QCIF(176x120 for NTSC, 176x144 for PAL) Bandwidth : 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M bps



	Frame rate : 1, 2, 3, 4, 5, 10, 15, 20, 25, 30 fps
Audio	Built-in audio line-in for audio monitoring Audio compression: MPEG2 audio, AMR-NB for 3GPP/ISMA(RTSP streaming)
Security	Web management username/password protection Video display ID/password protection
Installation, management and maintenance	Installation tool on CD and Web-based configuration Automatic configuration backup and restore Video management software-CamView for video access and multi-camera management Firmware upgrades via FTP
Minimum Web browsing and management software requirements	Built-in web server for standard web browser access Pentium 4(or equivalent AMD) CPU 1.0 GHz or higher,1 GB RAM
Supported protocols	IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, SNTP, FTP, DHCP, ARP, DNS, PPPoE, etc.
Video management software	Surveillance application for viewing and archiving up to 16 cameras
Users	Up to 20 simultaneous unicast users(depends on video settings)
Alarm and event management	Events triggered by video motion detection Notification/upload of JPEG images over FTP and/or email
Dimensions (HxWxD) and weight	40 x 81 x 92 mm, 300 g
Operating conditions	0-50°C Humidity 20 - 80% RH (non-condensing)

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434
Email: kitti@sone.co.th
www.sone.co.th